

DMD 831



Differential Pressure Transmitter with Display and Contact for Fluids and Gases

- ▶ 2 piezoresistive stainless steel sensors
- ▶ differential pressure from 0 ... 1 bar up to 0 ... 70 bar
- ▶ display mode selectable: P+, P-, ΔP
- ▶ display and pressure ports rotatable











Technical Data

Input pressure range								
Nominal pressure ¹	[bar]	1	2	3.5	7	20	35	70
Differential pressure range	[bar]							
TD 1:1		0 ... 1	0 ... 2	0 ... 3.5	0 ... 7	0 ... 20	0 ... 35	0 ... 70
up to		up to	up to	up to	up to	up to	up to	up to
TD 1:10		0 ... 0.1	0 ... 0.2	0 ... 0.35	0 ... 0.7	0 ... 2	0 ... 3.5	0 ... 7
¹ nominal pressure corresponds to the maximal permissible static pressure (one-sided)								
Analogue signal / Supply								
Standard	3-wire: 4 ... 20 mA				24 V _{DC} ± 10 %			
Permissible load	500 Ω							
Accuracy ²	≤ ± 1 % BFSL							
² accuracy according to IEC 60770 (non-linearity, hysteresis, repeatability)								
Contact								
Number, type	standard: 1 PNP				option: 2 independent PNP			
Max. switching current	125 mA, short-circuit proof							
Switching accuracy ²	≤ ± 0.5 % FSO							
Repeatability	≤ ± 0.1 % FSO							
Switching cycles	> 100 x 10 ⁶							
Delay time	0 ... 100 sec							
Programming								
Adjustability	analogue output / contact refers to: pressure "P+" or pressure "P-" or pressure difference							
	turn-down: max. 1:10							
Thermal error ³ (offset and span) / Permissible temperatures								
Tolerance band	≤ ± 1.5 % FSO							
TC, average	± 0.2 % FSO / 10 K							
In compensated range	0 ... 70 °C							
Permissible temperatures	medium: -40 ... 125 °C electronics / environment: -25 ... 85 °C storage: -40 ... 85 °C							
³ relating to nominal pressure range								
Electrical protection								
Short-circuit protection	permanent							
Reverse polarity protection	no damage, but also no function							
Electromagnetic compatibility	emission and immunity according to EN 61326							

DMD 831

Differential Pressure Transmitter

Technical Data

Mechanical stability		
Vibration	10 g RMS (20 ... 2000 Hz)	according to DIN EN 60068-2-6
Shock	100 g / 11 msec	according to DIN EN 60068-2-27
Materials		
Pressure port	stainless steel 1.4404 (316L)	
Housing	PA 6.6, Polycarbonate	
Seals	FKM	others on request
Diaphragm	stainless steel 1.4435 (316L)	
Media wetted parts	pressure port, seals, diaphragm	
Miscellaneous		
Display	4-digit, red LED-display, digit size 7 mm; range of indication -1999 ... +9999; accuracy 0.1 % +/- 1 digit; digital damping 0.3 ... 30 sec (programmable)	
Current consumption	max. 60 mA (without switching current)	
Weight	approx. 350 g	
Operational life	100 million load cycles	
Ingress protection (device)	IP 65	
Wiring diagram		
		
Pin configuration		
Electrical connections	M12x1 (5-pin), plastic	
Supply +	1	
Supply -	3	
Signal +	2	
Contact 1	4	
Contact 2	5	
Shield	via pressure port	
Mechanical connections (dimensions mm / in)		
standard		
		
option		
G1/2" DIN 3852		
		
G1/2" EN 837	G1/4" DIN 3852	G1/4" EN 837
		
1/2" NPT	1/4" NPT	

© 2020 BD|SENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

DMD831_E_061020

Tel.: +49 (0) 92 35 / 98 11- 0
Fax: +49 (0) 92 35 / 98 11- 11

www.bdsensors.de
info@bdsensors.de

BD|SENSORS
pressure measurement

Ordering code DMD 831

DMD 831

□	□	□	-	□	□	-	□	□	□	-	□	-	□	-	□	□	□	-	□	□	□	-	□	□	□	-	□	□	□
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

[illegible]