



Dew point and temperature probe DMP6

For dew point measurement in very high temperatures up to 350 °C

		Probe head and cable	Probe cable	Sensor type	Filter type	Operating pressure	Baud rate	Parity, data bit, stop bit	Probe Modbus address	Reserved	Probe mounting accessory	Connection cable
		DMPX	6	C	1	C	0			0		
1	Probe head and cable											
	DMP6 for very high temperatures	6										
2	Probe cable											
	Probe 6, 2m		C									
3	Sensor type											
	DrycapS			1								
4	Filter type											
	Grid filter for DMP6				C							
5	Operating pressure											
	Setting for ppm and other calculated variables											
	1 bar (absolute)					0						
6	Baud rate											
	1) 19200						A					
	9600						B					
7	Parity, data bit, stop bit											
	1) 8,N,2							0				
	8,E,1							2				
	8,O,1							4				
8	Probe Modbus address											
	1) 240								A			
	110								B			
	120								C			
	130								D			
	140								E			
9	Reserved											
	None									0		
10	Probe mounting accessory											
	None (installation in an existing cooling set)										0	
	Cooling set for DMP6, required for new installations										B	
11	Connection cable											
	None											0
	1,5m, open ends											1
	10m, open ends											2

1) Factory pre-set, can be changed in the field with a service cable (P/N 242659)

Probe can be connected to INDIGO series of transmitters regardless of the output configuration.

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings:

For use with INDIGO transmitters	DMPX	6	C	1	C	0	A	0	A	0	B	0
For use with Modbus RTU	DMPX	6	C	1	C	0	A	0	A	0	B	2

Valid from: December 2019