## SIGHT WINDOW

## Shows Level or Contents of Tanks, Pipelines; Fused Glass and Steel Construction



	Dime	Dimensions — Inches (mm)					
Model	Α	В	С	D	E		
SFI-550-1/4	1/4	11/32 [8.73]	5/8 ]15.95]	3/16 [4.76]	5/8 [15.95]		
SFI-550-3/8	3/8	7/16 [11.11]	3/4 [19.05]	7/32 [5.56]	23/32 [18.26]		
SFI-550-1/2	1/2	9/16 [14.29]	15/16 [23.81]	7/32 [5.56]	25/32 [19.84]		
SFI-550-3/4	3/4	3/4 [19.05]	1-1/16 [26.99]	5/16 [7.94]	15/16 [23.81]		
SFI-550-1	1	15/16 [23.81]	1-3/8 [34.93]	5/16 [7.94]	1-1/16 [26.99]		
SFI-550-1-1/4	1-1/4	1-3/16 [30.18]	1-3/4 [44.45]	13/32 [10.32]	1-7/32 [30.96]		
SFI-550-1-1/2	1-1/2	1-7/16 [36.53]	2 [50.80]	13/32 [10.32]	1-7/32 [30.96]		
SFI-550-2	2	1-7/8 [47.63]	2-1/2 [63.50]	13/32 [10.32]	1-9/32 [32.54]		

The SERIES 550 Sight Windows is a range of glass with plated steel body sight windows which display level or contents of tanks or pipelines. Connections are standard NPT in sizes ranging from 1/4 to 2".

## FEATURES/BENEFITS

- · Glass to metal bond for utmost reliability
- Plated steel bodies have convenient hex wrench surfaces for easy installation
- · Windows are clear, ripple free, and flush with the front face, with no recess on which dirt might collect

## **APPLICATIONS**

- Hydraulic tanks
- · Pressure vessels
- · Coolant tanks
- · Hydraulic lines
- · Oil reservoirs

SP	EC	; F	ICA	ш	NS

Service: Compatible gases and liquids.

Wetted Materials: Window: Glass; Body: Plated steel.

Temperature Limit: 200°F (93°C). Pressure Limit: 125 psig (8.6 bar). Connections: 1/4" to 2" male NPT.

MODEL CHART		
Model	Model	
SFI-550-1/4	SFI-550-1	
SFI-550-3/8	SFI-550-1-1/4	
SFI-550-1/2	SFI-550-1-1/2	
SFI-550-3/4	SFI-550-2	